
## New low temperature multidipole plasma device with a magnetic X-point and its properties

[Plasma Sources Sci. Technol. 29, 115012 (2020)]

#### Young-chul GHIM

Department of Nuclear & Quantum Engineering, KAIST, S. Korea



28th January 2021

@ International Online Plasma Seminar








## Co-authors and acknowledgements

- Co-authors
  - ✓ KAIST: Yegeon Lim (1st author), Yong Sung You, Wonjun Lee, Wonho Choe
  - ✓ Jeonbuk National Univ.: Se Youn Moon
  - ✓ Korea Institute of Fusion Energy (National Fusion Research Institute): Taihyeop Lho
  - ✓ Agency for Defense Development: HJ Woo
  - ✓ I.T.S.: Bosung Kim
- > Acknowledgements
  - ✓ National Research Foundation of Korea funded by the Ministry of Science and ICT
    - o NRF-2017M1A7A1A01015892
    - o NRF-2020M1A7A1A03016161
    - o NRF-2017R1C1B2006248
  - ✓ KAI-NEET, KAIST
- Many of the data and pictures presented here are from [Plasma Sources Sci. Technol. 29, 115012 (2020)]






## Prologue: Introducing MAXIMS (Magnetic X-point simlator system)







#### MAXIMUS – CAD drawing




- ➤ 60 [cm] Diameter and 2 x 100 [cm] chambers
- ➤ 1<sup>st</sup> chamber is grounded; while 2<sup>nd</sup> chamber is electrically isolated
- > Total 110 ports for various diagnostics and control purposes





## MAXIMUS – CAD drawing








## MAXIMUS – CAD drawing (half-cut)


Water-cooled, Teflon insulated copper tubes carrying DC currents








### MAXIMUS — Picture








#### Prologue: An example of low temperature plasmas with tokamak-like poloidal B-fields



By varying (decreasing) the strength of "poloidal magnetic fields"







#### Contents

- ➤ General descriptions of MAXIMUS
  - ✓ Structures of magnetic fields: 1) permanent magnets; 2) axial current
  - ✓ DC plasma sources: 1) end-plate ThW filaments; 2) core ThW filaments; 3) end-plate LaB<sub>6</sub> disk;
- ➤ Basic properties of MAXIMUS plasmas
  - ✓ Under the multidipole configuration
  - ✓ Under the poloidal magnetic fields configuration with X-point
- Motivation of building MAXIMUS
- > Summary





#### Contents


- General descriptions of MAXIMUS
  - ✓ Structures of magnetic fields: 1) permanent magnets; 2) axial current
  - ✓ DC plasma sources: 1) end-plate ThW filaments; 2) core ThW filaments; 3) end-plate LaB<sub>6</sub> disk;
- ➤ Basic properties of MAXIMUS plasmas
  - ✓ Under the multidipole configuration
  - ✓ Under the poloidal magnetic fields configuration with X-point
- Motivation of building MAXIMUS
- > Summary






#### MAXIMUS: Permanent magnets create multidipole configuration

<Side wall>




<End-plate wall>









#### MAXIMUS: Permanent magnets create multidipole configuration













#### MAXIMUS: A pair of axial currents create X-point configuration








- $\checkmark I_{axial} \le 1.0 kA$
- ✓ Currents: either parallel or anti-parallel






#### MAXIMUS: Measured (hall probe) total magnetic fields








#### MAXIMUS: Calculated total magnetic fields







## MAXIMUS: Available DC plasma source





- > Three types of sources
  - 1) End-plate wall ThW filaments
  - 2) Core ThW filaments
  - 3) LaB6 cathode (disk)






## Plasma sources: 1) End-plate ThW filaments













#### Plasma sources: 1) An example of plasmas with the end-plate ThW filaments








Plasma sources: 1) Examples of plasmas with the end-plate ThW filaments




## Plasma sources: 2) Core ThW filaments

- A problem with the end-plate ThW filaments: plasmas were not able to penetrate into the "core" region when the X-point configuration is generated.
- > Change the source region: Install a plasma source in the "core" region, then the plasmas will be "confined."
















#### Plasma sources: 2) A movie of plasmas with the core ThW filaments











By varying (decreasing) the strength of "poloidal magnetic fields" Iaxial (top) =  $1.0 \rightarrow 0$  kA (varied) Iaxial (bottom) = 1.0 kA (fixed)








## Comparison between the end-plate and core filaments








## Plasma sources: 3) End-plate LaB<sub>6</sub> disk.









## Plasma sources: 3) End-plate LaB<sub>6</sub> disk.











Nuclear Fusion&Plasma Lab













#### Plasma sources: 3) Example of plasmas with the end-plate LaB<sub>6</sub> disk






- ✓ Operation limit
  - o Heating power
    - $-P_h = 5kW$
  - o Discharge condition
    - $-I_d = 50A, V_d = -200V$











#### Contents


- General descriptions of MAXIMUS
  - ✓ Structures of magnetic fields: 1) permanent magnets; 2) axial current
  - ✓ DC plasma sources: 1) end-plate ThW filaments; 2) core ThW filaments; 3) end-plate LaB<sub>6</sub> disk;
- ➤ Basic properties of MAXIMUS plasmas
  - ✓ Under the multidipole configuration
  - ✓ Under the poloidal magnetic fields configuration with X-point
- Motivation of building MAXIMUS
- > Summary








## Langmuir probes measure plasma properties

<Three sets of Langmuir probes>










<An example of IV curve from MAXIMUS plasmas>





(c)




# Data obtained with the end-plate ThW filaments






### Multidipole vs non-multidipole plasmas ( $I_{axial} = 0.0 \text{ kA}$ )

Ar neutral pressure : 1.00 mTorr; Discharge (bias) voltage: -80.0 V; Discharge current = 0.5 A



Juclear Fusion&Plasma Lab

< Verifying the Boltzmann electrons >



$$\langle T_{eff} \rangle_{|x| < 22.0cm} = 1.764 \pm 0.036 \text{ eV}$$


$$T_e^{Boltzmann} = 1.773 \pm 0.005 \text{ eV}$$


→Indicating that measurements of  $\phi_p$ ,  $n_e$  and  $T_{eff}$  are consistent.




29 / 40 Prepared by Y.-c. GHIM

## 2D profiles of plasmas are obtained at z=50 [cm]












#### Plasma properties are correlated with the poloidal B-fields

Ar neutral pressure : 1.00 mTorr; Discharge (bias) voltage: -100.0 V; Discharge current = 0.2 A



- Densities, temperatures and absolute values of floating potentials are smaller in the core region (consistent with the visual pictures, i.e., no plasmas in the 'core' region as B-fields increase)
- As plasmas are produced in the 'edge' region, it becomes more difficult for plasmas to penetrated into the 'core' region as B-field increases as if there exists a transport barrier.





## Data obtained with the core ThW filaments


#### Note:


- Some of the data we show are not fully validated, thus credibility of the analyzed data may be questionable.
- Consider what I show is just preliminary results to stimulate further discussions.






#### Electrons are strongly drifting in the e-grad-B and curvature drift direction









- Plasmas are only generated in one side of the core ThW filaments
  - ✓ As the bias voltage on the filaments increase, the size of plasma column in axial direction increases.
  - The direction corresponds to the electron grad-B and curvature drift. (Note: electrons are most likely to be magnetized while ions are not.)


B=10G; L <sub>∇B</sub> =10cm	Thermal e-	Primary e-	Ar <sup>+</sup>
Temperature [eV]	~1	~100	~0.025
$v_{th}$ [m/s]	$\sim 4.2 \times 10^5$	~4.2x10 <sup>6</sup>	~250
$f_{ce}\left[\mathrm{Hz} ight]$	~28M	~28M	~400
r <sub>L</sub> [cm]	~0.24	~2.4	~10
$v_{\nabla B} + v_{curv} \text{ [m/s]}$	~104	~106	~250






### Radial profiles (in the core region) depend on neutral pressures

Varying Ar neutral pressure; Discharge (bias) voltage: -100.0 V; Discharge current = 1.0 A;  $I_{ax}^{top} = I_{ax}^{bottom} = 0.50 \text{ kA}$ 





- Stiff gradients are observed for small neutral pressures (less collisions leading smaller diffusivity allows the gradient to be sustained by the B-fields).
- Unusually (absolute) large floating potentials (compared to no poloidal B-field) are observed which can be explained by large amount of high energy electrons due to the drifting motions.





#### Up-down symmetry at smaller radial position with smaller poloidal B-fields


Core region

y=8cm, radial profile

y=-8cm, radial profile Private region

x [cm]

Ar neutral pressure: 1.00 mTorr; Discharge (bias) voltage: -80.0 V; Discharge current = 1.0 A








- Plasma source only exists in the core region (around the top copper tube)
  - ✓ Top (y=8cm) and bottom(y=-8cm) plasmas become 'similar' at the smaller radial location when the poloidal B-fields are smaller
  - ✓ This may be explained by easier diffusion with smaller B-fields.
  - ✓ Perhaps, this can be used to measure the particles (or heat) diffusivity.






## Flattened plasma profiles around the magnetic X-point

Ar neutral pressure: 1.00 mTorr; Discharge (bias) voltage: -150.0 V; Discharge current = 1.0 A





- As we've seen consistently, profiles are stiffer for stronger poloidal B-fields.
- ➤ Profiles are flattened around the X-point indicating increased transport levels around the X-point. (B-fields are weak around the X-point.)






#### Contents

- General descriptions of MAXIMUS
  - ✓ Structures of magnetic fields: 1) permanent magnets; 2) axial current
  - ✓ DC plasma sources: 1) end-plate ThW filaments; 2) core ThW filaments; 3) end-plate LaB<sub>6</sub> disk;
- ➤ Basic properties of MAXIMUS plasmas
  - ✓ Under the multidipole configuration
  - ✓ Under the poloidal magnetic fields configuration with X-point
- Motivation of building MAXIMUS
- > Summary





### To investigate role of neutrals in a tokamak scrape-off layer



- Neutrals in the scrape-off layer (SOL)
  - ✓ act as sources/sinks of particles, momentum and energy
  - are correlated with shear flow which is a widely accepted key parameter for low and high confinement mode transitions
  - ✓ plays an important role for generating detached plasmas (from divertors) which reduces heat loads to the divertor
  - ✓ may cause (through sudden H-L back transition) or mitigate/prevent disruption events through recycling processes
  - ✓ are considered to be a hidden variable





#### To investigate fundamental physics of non-Maxwellian electrons

- $\triangleright \nabla B$  and curvature drifts not only shifts the EVDF, but they also generate skewness and excess kurtosis.
  - ✓ This is because these drifts depend on a speed of an individual particle.
  - ✓ We can control levels of skewness and excess kurtosis in some degrees.
  - ✓ We are interested in investigating how various physics such as diffusion process, plasma waves and nonlinear physics (solitons, shock-wave, etc.) depend on skewness and excess kurtosis of EVDF.
- Some of interesting phenomena observed in solar corona, solar wind, space plasmas, magnetic reconnection are high energy density plasmas are theoretically explained with non-Maxwellian EVDFs.
  - ✓ We plan to design experiments to investigate such interesting phenomena with MAXIMUS.





## Summary

- ➤ We have introduced our linear plasma system MAXIMUS which can generate
  - ✓ Tokamak-like poloidal magnetic fields with an X-point configuration
    - o Thus, MAgnetic X-point sIMUlator System
- > We have introduced you three types of plasma sources with characteristics of generated plasmas
  - 1) End-plate ThW filaments
  - 2) Core ThW filaments
  - 3) End-plate LaB<sub>6</sub> disk
- We have presented how plasma profiles are affected by poloidal magnetic fields.

## Thank YOU!



